







#### Construction:

Shelter made of steel rectangular or square profile section, hot dib glvanized acc. to ISO EN 1461 and electrostatical powder painted acc. to each color of RAL Standard pallette

#### Models and Dimensions:

Available in 2 different length depending on the amount of units:

- model 203 2 units
- model 205 3 units
- model 207 4 units

This model is avalaible with three types of side walls:

- full size side wall 1365 mm (standard)
- narrow side wall 970 mm (optional)
- side wall with advertising display 1365 mm (optional)
- no side wall cantilevered model (optional)

# Types of infills:

Roof - flat roof with 10mm polycarbonate sheet, dimmed or with security VSG glass 10mm (2x5mm) (optional)

Walls - 8 mm toughened glass

#### Seating bench:

Shelter is offered without bench. Benches are optional and avalaible in 3 types of seats:

- freestanding bench with wooden planks (optional)
- freestanding bench with laminated planks (optional),
- freestanding individual injected moulded plastic seats (optional).

## Back support over the seating bench:

Shelter without back support.

### Optional equipment:

- advertising display case 1,2 x 1,8m (lightened or not) with a possibility of universal assembly within each unit of the shelter (each back and side unit),
- informational display case with lock, dimmensions 1260 x 700mm or 700 x 700mm
- bus stop sign,
- name of the bus stop,
- recycled waste bin (freestanding or assembled to the shelter construction),
- ashtray with waistbin for smokers
- bus driving schedule in format A4, A3 or A2
- -ready point concrete froundation (1 pcs for each post) or reinforced concrete plate thicknesss 12 cm.